

Fieldmarshal

SHRIDEV 



SHRIDEV 112

SHRIDEV 115

SHRIDEV 120

**“Shridev – Where Innovation Meets
Cultivation.”**

TRACTOR LEAFLET

SHRIDEV 112

specifications



ENGINE	
Type	Direct Injection
Horse Power	12 H.P.
Bore Stroke	92 / 92 mm
Capacity	611 Cc
Cylinder	Single Cylinder Water Cooled
TRANSMISSION	
Type	Sliding Mesh
Gear	6 Forward
Speed	3 Reverse
Max. Forward	24.8 Km. / Hr.
Max. Reverse	2.5 Km. / Hr.
DIMENSION	
Length	2200 mm
Width	900 mm
Height	1540 mm
Ground Clearance	220 mm
Wheel Base	1300 mm
WEIGHT OF TRACTOR	
Without Ballast	630 Kg.

TYRE SIZE	
Front	4.50 x 10
Rear	6.00 x 16
BRAKE	
Type	Disc Brake
P.T.O. - R.P.M.	540
ELECTRICAL SYSTEMS	
Battery	12 Volt 55 A.H.
Alternator	12 Volt 43 Amp.
CLUTCH	
Type	Dry, Fiction Plate
Size	180 mm
HYDRAULIC SYSTEM	
Type	Position & Draft Control
Pump	Gear Type
Lifting Capacity	500 Kg. (On 3 Point Linkage)
WHEEL TRACK	
Size available	24" (610mm) 28" (700 mm) 30" (750 mm) 38" (950 mm)

SHRIDEV 115

specifications



ENGINE	
Type	Direct Injection
Horse Power	15 H.P.
Bore Stroke	100 / 110 mm
Capacity	863.5 cc
Cylinder	Single Cylinder Water Cooled
TRANSMISSION	
Type	Sliding Mesh
Gear	6 Forward
Speed	3 Reverse
Max. Forward	26.5 Km. / Hr.
Max. Reverse	5.5 Km. / Hr.
DIMENSION	
Length	2550 mm
Width	1220 mm
Height	1860 mm
Ground Clearance	265 mm
Wheel Base	1490 mm
WEIGHT OF TRACTOR	
Without Ballast	823 Kg.

TYRE SIZE	
Front	5.20 x 14 (8 P.R.)
Rear	8.00 x 18 (4 P.R.)
BRAKE	
Type	Disc Brake
P.T.O. - R.P.M.	540
ELECTRICAL SYSTEMS	
Battery	12 Volt 70 A.H.
Alternator	12 Volt 43 Amp.
CLUTCH	
Type	Dry, Fiction Plate
Size	200 mm
HYDRAULIC SYSTEM	
Type	Position & Draft Control
Pump	Gear Type
Lifting Capacity	600 Kg. (On 3 Point Linkage)
WHEEL TRACK	
Size available	24" (610mm) 28" (700 mm) 30" (750 mm) 38" (950 mm)

SHRIDEV 120

specifications



ENGINE	
Type	Direct Injection
Horse Power	18 H.P.
Bore Stroke	100 / 114 mm
Capacity	895 Cc
Cylinder	Single Cylinder Water Cooled
TRANSMISSION	
Type	Sliding Mesh
Gear	6 Forward
Speed	3 Reverse
Max. Forward	26.5 Km. / Hr.
Max. Reverse	5.5 Km. / Hr.
DIMENSION	
Length	2550 mm
Width	1220 mm
Height	1860 mm
Ground Clearance	265 mm
Wheel Base	1490 mm
WEIGHT OF TRACTOR	
Without Ballast	850 Kg.

TYRE SIZE	
Front	5.20 x 14 (8 P.R.)
Rear	8.3 x 20 (4 P.R.)
BRAKE	
Type	Disc Brake
P.T.O. - R.P.M.	540
ELECTRICAL SYSTEMS	
Battery	12 Volt 70 A.H.
Alternator	12 Volt 43 Amp.
CLUTCH	
Type	Dry, Fiction Plate
Size	200 mm
HYDRAULIC SYSTEM	
Type	Position & Draft Control
Pump	Gear Type
Lifting Capacity	600 Kg. (On 3 Point Linkage)
WHEEL TRACK	
Size available	24" (610mm) 28" (700 mm) 30" (750 mm) 38" (950 mm)

Manufacturer & Exporter : AN ISO 9001:2015 Certified Company

P. M. DIESELS PVT. LTD.

P. B. No. : 1003, Aji Industrial Estate, RAJKOT - 360 003 - Gujarat (INDIA)

Whatsapp Business No.: +91 90235 50564 CIN : U29195GJ1980PTC003918

E-mail : contactus@fieldmarshal.com Web : www.fieldmarshal.com

Follow us at : Fieldmarshal-PMDL Mob. No. : +91 91068 82861

As continuous improvements are contemplated the illustration and description are not binding
(This artistic / literary work is in the sole ownership of P. M. Diesels Pvt. Ltd. infringement / Un authorised copying of this artistic work is an offence under the provisions of Copy Right Act. 1957)