



Strong Build. Smart Flow. Trusted Performance.

MONOBLOCK PUMPS



EUFM MONOBLOCK PUMPS

technical data

Pump Type	Power Range (HP)	Max Head (Meters)	Suction Lift (Meters)	Best Application
Self-Priming Monoblock	0.5 HP – 1.0 HP	6 – 36	7 – 8	Apartments & Bungalows
Self-Priming Jet	0.5 HP – 1.5 HP	12 – 45	8 – 15	High-pressure supply
Regenerative (Non-Self-Priming)	0.25 HP – 1.0 HP	6 – 50	7 – 8	High-rise lift (Vertical)
Shallow Well Jet	0.5 HP – 1.5 HP	15 – 40	9 – 25	Open wells & Sumps

key advantages

Self-Priming Monoblock Pumps

- High-grade aluminum/cast iron body for heat dissipation.
- Fitted with Thermal Overload Protector (TOP) to prevent motor burnout.

Self-Priming Jet

- Pumps-Robust design with high-quality mechanical seals.
- Enhanced suction capacity compared to standard monoblocks.

Non-Self-Priming / Regenerative Pumps

- Compact, space-saving design.
- Energy-efficient motor with low power consumption.

Shallow Well Jet Pumps

- Heavy-duty construction for continuous operation.
- Easy maintenance as the pump stays above ground.